

# We Are All About Getting the Job Done. **For Less**.

The Solideal WL offers the best performance when it comes to heavy duty conditions. That means that whatever the terrain, you'll get the job done efficiently. That's productivity. That's our Lowest Operating Cost Solution (LOCS).





- Provides 20% more durability
- Provides superior stability and comfort
- Carcass resistance up to three times the nominal inflation pressure

### Deep Lug Depth

- Enhanced durability and wear for long life
- High tread wearable volume for excellent traction on all surfaces

### Advanced Rubber Compound

 Improved cut and chip resistance with no delamination

# Optimized Sidewall and Bead Construction

 Increased machine stability for enhanced safety and comfort








# Additional Facts About the Solideal WL

**Tires for Wheel Excavators** 

## **Tire Specifications**

TIRE SIZE	PR	TT/	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inch]			LOAD INDEX	SPEED SYMBOL	MAXIMUM TIRE LOAD [kg] [ <i>lb</i> ]				
		TBLS								STATIC		16 km/h <i>10 mph</i>		
			Recommended	Alternative	O.D.	O.W.	O.T.D. [mm] [32nd]			Static	0-8 km/h <i>0-5 mph</i>	10 km/h <i>6 mph</i>	25 km/h 16 mph	45 km/h 28 mph
8.25-20	14	TT	6.50	7.00	1000	252	26	148	A2	6105 13500	3645 8050	3150 <i>6950</i>	2600 <i>5750</i>	2325 5150
					39.4	9.9	33			9.00 bar 129 PSI	8.00 bar 114 PSI		7.50 bar 107 PSI	
9.00-20	14	тт	7.00	6.50/7.50	1039	267	27	153	A2	6990 15450	4170 9200	3605 7950	2975 6550	2660 5850
					40.9	10.5	34			8.50 bar 121 PSI	7.50 bar 107 PSI		7.00 bar 100 PSI	
10.00-20	16	тт	7.50	7.00/8.00	1070	284	26	158	A2	8215 18150	4900 10800	4240 9350	3500 <i>7750</i>	3125 6900
					42.1	11.2	33			8.50 bar 121 PSI	8.00 bar 114 PSI		7.50 bar 107 PSI	
11.00-20	16	тт	8.00	8.50	1064	280	25	160	A2	8700 19200	5200 11500	4500 <i>9950</i>	3700 <i>8150</i>	3300 <i>7300</i>
					41.9	11.0	31.5			8.50 bar 121 PSI	7.75 bar <i>111 PSI</i>		7.00 bar 100 PSI	

# Tread Aspects Solideal WL Competitor



**Authorized Distributor:** 

